

S

C

2



## **AERO TAPE**

Flexible, cuttable and dimmable tape. Pre-wired tape, simple and quick installation. Easy to mount on smooth surfaces thanks to high quality 3M tape at the back.

One BIN Only to ensure perfect color consistency









### **AERO TAPE**

-With 120 high quality 2835 LEDs per meter and a width of 10mm.

- -Running on 24 VDC, it is designed to use no more than 24 Watts /m.
- -Wide color temperature range for your option. -Long lifespan and excellent in heat dissipation.
- -Use SDMC3 2835 LEDs in One BIN Only to ensure perfect color consistency -High CRI90 to present real color, CRI80 is optional to meet your needs.
- Product Benefits:

#### -Flexible, cuttable and dimmable LED strip.


- -Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back.
- -Pre-wired LED strip, simple and quick plug-and-play installation.



#### **Electrical data**

Voltage	DC24V (23.5V <sub>min</sub> , 24.5V <sub>max</sub> )			
LED PIN Temperature	Max. 60.9°C /141.6°F			
Storage Temperature	-25°C /-13°F <sub>min</sub> , 60°C /140°F <sub>max</sub>			
Lumen Efficiency	100lm/w(4000K)			
SDCM	3 ( 2700K, 3000K, 4000K)			
Ra	Ra90; Ra80 optional			
Max Current/LED	50mA			
Unit Cut	50mm			
Waterproof Rate	IP20			
Warranty	5 Years			

LM/M	4.8W	9.6W	14.4W	19.2W	24W
2700K	450	899	1320	1858	2200
3000K	465	917	1385	1898	2289
3500K	470	940	1390	1901	2310
4000K	481	965	1450	1970	2380
6500K	507	970	1457	1986	2350
Max. Run Length(M)	5	5	5	5	5



Life span> 54000H

One Bin Only

ĺΠ


Indoor

#### Important notice

-The given data are typical values due to the tolerances of the production process and the electrical components, values for light output and electrical power can vary up to 10%.




#### Order code



#### **Accessories**

Art.#	Description	Picture	Art.#	Description	Picture
C0001	Connector for Strip to strip connection, IP20		T0001	VHB 3M adhesive tape	
C0002	Connector for Strip to cable connection, IP20		XLG-150- 24-A	PSU 24V/150W IP67, Non- dimmable, White, 100-305V supply	
MF001	Male and Female connector, IP20		ELG-150- 24B	PSU 24V/150W IP67, 3 in 1 dimming function, White, 100- 305V supply	
MF002	Male and Female DC connector, IP44	and a	ELG-150- 24DA	PSU 24V/150W IP67, Non- dimmable, White, 100-305V supply	

### Wiring connection



#### Application



Where to use the product? It can achieve fantastic lighting effects for almost all your indoor projects, effectively and elegantly highlighting certain areas with charming lighting for your project. Its excellent flexibility and cuttability offer many possibilities and great freedom of design. Full color range to meet your different lighting needs.

same time.

POWER
048=4.8W
096=9.6W
144=14.4W
192=19.2W
240=24W

Eg1: AERO TAPE-27-05000-048: AERO TAPE, 2700K, 5M/reel, 4.8W/m.

Eg2: AERO TAPE-30-05000-096: AERO TAPE, 3000K, 5M/reel, 9.6W/m.

It is an ideal indoor lighting option for offices, corridors and residential, shopping mall interiors....all in all, almost all interiors can be lighted up and beautified by creating stylish lighting effects which can Brighten your world and mood at the

# Begmever

+ DC24

Address: 100 N Howard St Ste R, Spokane, WA, 99201-0508 USA Tel: 323-5104660 info@beamever.com www.beamever.com