

# Beamever

## LED CLICK LINE

Pre-wired LED fixture, simple and quick plug-and-play installation. Complete smart accessories let you freely to create your desired lengths and shapes.

One BIN Only to ensure perfect color consistency






## LED CLICK LINE

- Slim in size 12.5x13mm(WxH) / 0.49"x0.51"(WxH).
- With high quality LED to offer long lifespan.
- 2-Step MacAdam bin and One BIN Only to ensures perfect color consistency.
- Complete smart accessories let you freely to create your desired lengths and shapes.
- Pre-wired LED fixture, simple and quick plug-and-play installation.
- Could go 8M Max. with one end power supply without brightness attenuation.


### Product Benefits:

- Homogeneous light effect & high light efficiency.
- Long lifespan and excellent in heat dissipation.
- A ready-to-install product to ensure simple and error-free installation.



## Electrical data

Voltage	DC24V (23.5V <sub>min</sub> 24.5V <sub>max</sub> )
LED PIN Temperature	Max. 65°C /149°F
Storage Temperature	-25°C /-13°F <sub>min</sub> 45°C /113°F <sub>max</sub>
Lumen Efficiency	80lm/w(4000K)
Ra	Ra>90
SMD Type	Lumileds 2835
Beam Angle	120°
IP Rate	IP20
Warranty	5 Years



LM/unit	LCL-100	LCL-200	LCL-500	AC01	AC02	AC03	AC04	AC05	AC06
2700K	100	190	480	160	150	160	320	250	180
3000K	100	190	480	160	150	160	320	250	180
3500K	100	190	480	160	150	160	320	250	180
4000K	100	190	480	160	150	160	320	250	180
6500K	100	190	480	160	150	160	320	250	180
Wattage (W)	1.2	2.5	6	2.4	2.4	2.4	4.8	3.6	3.6
Max. Run Length (M)	8	8	8	/	/	/	/	/	/

### Important notice

- LCL-100 refer to LED CLICK LINE in 100mm, LCL-200 refer to LED CLICK LINE in 200mm, LCL-500 refer to LED CLICK LINE in 500mm.
- Max. run length refers to single side feed in serial connection.
- Due to the tolerances of the production and electrical components, output power can vary up to 10%.




## Order code

SERIES NAME	COLOR	LENGTH	POWER
LED CLICK LINE	27= 2700K	100=0.1M/3.94"	012=1.2W
	30= 3000K	200=0.2M/7.87"	025=2.5W
	35= 3500K	500=0.5M/19.68"	060=6W
	40=4000K		
	65=6500K		


Eg1:  
LCL-27-100-012  
LED CLICK LINE, 2700K, 0.1M/unit,  
1.2W/unit

Eg2:  
LCL-30-500-060  
LED CLICK LINE,3000K, 0.5M/unit,  
6W/unit


## Play and Plug




## Various Installation Way



## Order code




## Order code




Cross connector  
Order Code: AC01

Seamless connection thanks to various smart connector. Simple DIY connection makes installation interesting.




T shape connector  
Order Code: AC02

Seamless connection thanks to various smart connector. Simple DIY connection makes installation interesting.




L shape flat connector  
Order Code: AC04

Seamless connection thanks to various smart connector. Simple DIY connection makes installation interesting.




L shape light in connector  
Order Code: AC05

Seamless connection thanks to various smart connector. Simple DIY connection makes installation interesting.



L shape light out connector  
Order Code: AC06


Seamless connection thanks to various smart connector. Simple DIY connection makes installation interesting.




Rotation corner  
Order Code: AC03

Seamless connection thanks to various smart connector. Simple DIY connection makes installation interesting.


## Order code




Cross connector  
Order Code: AC01  
Dimension: 180×180×13mm/  
7.08"×7.08"×0.51"(L×W×H)  
Material: aluminium



T shape connector  
Order Code: AC02  
Dimension: 180×96.3×13mm/  
7.08"×3.79"×0.51"(L×W×H)  
Material: aluminium



L shape flat connector  
Order Code: AC04  
Dimension: 100×100×13mm/  
3.94"×3.94"×0.51"(L×W×H)  
Material: aluminium




L shape light in connector  
Order Code: AC05  
Dimension: 100×100×12.5mm/  
3.94"×3.94"×0.49"(L×W×H)  
Material: aluminium



L shape light out connector  
Order Code: AC06  
Dimension: 100×100×12.5mm/  
3.94"×3.94"×0.49"(L×W×H)  
Material: aluminium



Rotation corner  
Order Code: AC03  
Dimension: 215×12.5×13mm/  
8.46"×0.49"×0.51"(L×W×H)  
Material: aluminium



Close end cap  
Order Code: AC07



Fixed bracket  
Order Code: AC08



Angle bracket  
Order Code: AC09



Magnet board  
Order Code: AC10




Joint connector-LCL to LCL  
Order Code: AC11



Extension cable-L145mm  
LCL to LCL  
Order Code: AC12



Extension cable-  
L1500mm  
LCL to LCL  
Order Code: AC13



Distribution cable-150mm  
Distribution box to cable  
Order Code: AC14

## Order code



Distribution cable-L1500mm  
Distribution box to cable  
Order Code: AC15



Power cable-L150mm  
Order Code: AC16



Power cable with DC connector-  
L150mm  
Order Code: AC17



Power cable with DC connector-  
L1500mm  
Order Code: AC18



Distribution box connector (with 6  
channels)  
Order Code: AC19



Distribution box open wire (with 6  
channels)  
Order Code: AC20



Constant Voltage LED Driver  
Non-Dimmable  
AC220-240V DC24V 30W  
Order Code: UT24V-30W



Constant Voltage LED Driver  
Non-Dimmable  
AC220-240V DC24V 75W  
Order Code: Q8H-24V-75W



Constant Voltage LED Driver  
Non-Dimmable  
AC220-240V DC24V 150W  
Order Code: Q8H-24V-150W




Constant Voltage LED Driver  
Dimmable  
AC220-240V DC24V 150W  
Order Code: Q8H-24V-150W



Dimmable LED Controller  
10-24VDC  
Order Code: C5AD-DALI CV




85-132VAC/170-264VAC by  
switch DC24V 150W IP20  
Global certification  
Order Code: LRS-150-24



## Application

It is a complete linear lighting fixture. With its various smart accessories, you can create lighting in different shapes for your unique projects. It can bring homogeneous lighting to your projects. It is a fantastic lighting products for retail shops, KBB, gallery, show-booth and exhibition room Besides, it has perfect good performance in jewelry cabinet, commodity display cabinet and interior furniture. Last but not least, it is desired light in bar counters, restaurants, and hotels.

## Order code





**Beamever**

Address: 100 N Howard St Ste R,  
Spokane, WA, 99201-0508 USA  
Tel: 323-5104660  
info@beamever.com  
www.beamever.com