


AERO TAPE SAUNA

Indoor · White · High-temperature

Beamever

Features

- Field cuttable
- Operates in temperature up to 100°C (212°F)
- Slim and elegant, ideal for indoor applications
- 3M tape on the back makes it easy to install
- Available in a variety of CCT color options
- 5 years warranty



Fixture type	
Project name	
Project phase	
Date	



Dimension & Bending



Physical

PCB Width	10mm
LED Pitch	12.5mm
Cutting Interval	50mm
LED Brand	Sanan
LED Size	2835
LED Quantity	120 LEDs/m
Housing Material	N/A
Adhesive Type	Yellow 3M tape
Feed Entry	Front
Feed Length	Standard length 15cm
Storage Temperature	-25~100°C (-13~212°F)
Ambient Temperature	-25~100°C (-13~212°F)
Max Production Length	30m

Performance & Electrical

Voltage	24VDC (23.5Vmin, 24.5Vmax)
Beam Angle	120°
MacAdam	3 steps
Efficacy (lm/W)	178lm/W @4000K 9.6W
CRI	Ra80
Lumen Maintenance	> 54,000 hours
IP Rating	IP65
Resistance	UV, solvent, saltwater, flame
Dimming	Triac, ELV, PWM, 0-10V, DMX
Control Protocol	N/A
Warranty	5 years

Certification & Safety

Certifications	UL, CE, REACH, RoHS, CB
Environment	Dry, damp locations

Lumen/m	4.8W	9.6W
■ 2700K	782	1565
■ 3000K	830	1660
■ 4000K	854	1709
■ 5000K	854	1709
■ 6500K	854	1709
Max. Run Length (m)	5	5

AERO TAPE SAUNA

Indoor · White · High-temperature



Order Code



Series	Temp./Color	Power	Feed Entry	Connector Wire	IP Rating	Length (mm)
AEROS	27=2700K 30=3000K 40=4000K 50=5000K 65=6500K	048=4.8W 096=9.6W	FF=Front + Front FC=Front + Closed	OW=Open wire 3.28' MFC=Male & female connector 0.98'	65=IP65	Min. - 50mm Max. run - 5000mm Cut Inc. - 50mm

Example: AEROS-30-048-FF-OW-65-05000

* Customizable—Contact Beamever representatives




*This product is not rated as submersible. Do not install in a location where water may pool or collect.

Mounting Options






* Standard length is 1m/pcs.

Name	Straight alluminum channel
Code	BE1202
Material	Alluminum
Mounting style	Surface mounted
Length	1m
Width	17.3mm
Height	14.5mm
Internal width	12.5mm






* Standard length is 1m/pcs.

Name	Straight alluminum channel
Code	BE1201
Material	Alluminum
Mounting style	Recessed mounted
Length	1m
Width	17.3mm
Height	14.5mm
Internal width	12.5mm



* Standard length is 1m/pcs.

Name	Straight alluminum channel
Code	BE1203
Material	Alluminum
Mounting style	Angled mounted
Length	1m
Width	18.1mm
Height	18.1mm
Internal width	12.5mm



* Standard length is 1m/pcs.

* For more options, please refer to "Beamever Profile Spec Sheet"

Name	Straight alluminum channel
Code	BE5615
Material	Alluminum
Mounting style	Mud-in
Length	1m
Width	15.5mm
Height	15mm
Internal width	12.5mm

Driver Options

Code	Max Load	Input	Output	Dimming	Environment	Size
XLG-150-24-A	150W	100-305VAC	24VDC	Non-Dim	Dry/Damp/IP67	180x63x35.5mm (L x W x H)
ELG-150-24B-3Y	150W	100-305VAC	24VDC	3 in 1 dimming	Dry/Damp/IP67	219x63x35.5mm (LxWxH)
ELG-150-24DA-3Y	150W	100-305VAC	24VDC	DALI control technology	Dry/Damp/IP67	219x63x35.5mm (L x W x H)
LPV-150-24	150W	180-305VAC	24VDC	Non-Dim	Dry/Damp/IP67	148x40x30mm (L x W x H)
LRS-150-24	150W	85-132V / 170-264VAC	24VDC	Non-Dim	Dry	99x97x30mm (L x W x H)
PWM-120-24	120W	90-305V / 127-431VAC	24VDC	3 in 1 dimming	Dry/Damp/IP67	191x63x37.5mm (LxWxH)

* Please refer to the spec sheet of each power supply for more detailed information

Accessories Options (Optional)



Name Mounting clip
Code AERO-MC-12
Mounting clip for SMD series, IP65




Name Silicone closed end cap
Code AERO-SEC-C-12
Closed silicone end cap, IP65



Name Silicone glue
Code SG
Silicone glue

Wiring Diagram

Non Dimmable



Dimmable

