

ANNO TAPE TW Indoor · Tunable White

Features

- Max run length up to 5m (16.4ft) from single power feed
- Field cuttable & joinable
- Low voltage DC24V
- 1400 lumen outputs
- IP20 rated, ideal for indoor uses
- 5 years warranty




Date _____ Fixture type _____

Project name _____ Project phase _____



Dimension



Order Code

Series	Environment	Voltage	Temp./Color	Power
ANNO	D2 Dry (IP20)	24 DC24V	2765 2700K+6500K	150 15W/M -1400 lm/M

Assembly Builder

Left Feed Entry				Right Feed Entry				Illuminated Length ¹		
F	Front	OW	Open wire 30cm	F	Front	OW	Open wire 30cm	Max.	5m	-15W
C	Closed	MC	Male connector with 30cm cable	C	Closed	MC	Male connector with 30cm cable	Increment	27.8mm	
		FC	Female connector with 30cm cable			FC	Female connector with 30cm cable			
		NA	Only for Closed Feed Entry			NA	Only for Closed Feed Entry			

Temp./Color	15W/M
2700K	644
6500K	814
2700K+6500K	1403
Max. Run Length (M)	5
Storage Temperature	-25-60°C
Ambient Temperature	-20-45°C

Technical Details

Width	10mm (0.39")
PCB Width	10mm (0.39")
LED Quantity	576 LEDs/M (175 LEDs/ft)
Beam Angle	180°
Efficacy	93.5lm/W @2700K+6500K 15W
CRI	Ra ≥ 90
Lumen Maintenance	> 54,000 hours
Max. Length Per Reel	30M (98.4')

Feed Entry Options



Connector Wire Options




ANNO TAPE TW

Indoor · Tunable White


Channel Compatibility

: No pixelation


Universal



Architectural




Main lighting



ANNO TAPE TW

Indoor · Tunable White


Special lighting



: Slight pixelation

Universal

BE2601



Drivers Options


Code	Max Load	Input	Output	Dimming	Environment	Size (L*W*H)
XLG-150-24-A	150W	100-305VAC	24VDC	Non-Dim	Dry/Damp/IP67	180 * 63 * 35.5 mm
ELG-150-24B-3Y	150W	100-305VAC	24VDC	3 in 1 dimming	Dry/Damp/IP67	219 * 63 * 35.5 mm
ELG-150-24DA-3Y	150W	100-305VAC	24VDC	DALI control technology	Dry/Damp/IP67	219 * 63 * 35.5 mm
LPV-150-24	150W	100-277VAC	24VDC	Non-Dim	Dry/Damp/IP67	148 * 40 * 30 mm
LRS-150-24	150W	85-132VAC / 170-264VAC	24VDC	Non-Dim	Dry	99 * 97 * 30 mm
PWM-120-24	120W	90-305VAC / 127-431VAC	24VDC	3 in 1 dimming	Dry/Damp/IP67	191 * 63 * 37.5 mm

DMX Decoders & Controllers Options

Type	Code	Description	Environment	Size (L*W*H)
DMX Decoders	LT-903	3 channels output, Max. 8A current per channel, up to 576W output power	Indoor	122 * 110 * 3 mm
Controllers	M2+M3-3A	3 channels output, Max. 3A current per channel, up to 216W output power	Indoor	135 * 30 * 20 mm
Controllers	GA2	512 DMX channels, 4 touch sensitive buttons (on/off, mode, previous, next)	Indoor	87 * 110 * 10 mm
Controllers	CW4	1024 DMX channels, 6 SECne buttons and a color wheel, ideal for hotels, homes and public	Indoor	145 * 107 * 10 mm

Wiring Diagram

Dimmable



ANNO TAPE TW Indoor · Tunable White

Connectors (Optional, purchase for extra)



NCO-STCN-3P-10
Strip to cable connector without wire, for 10mm (0.39") tape, 3 pin



NCO-STC-3P-10
Strip to cable connector with 15cm (5.91") wire, for 10mm (0.39") tape, 3 pin



NCO-STSJ-3P-10
Strip to strip jumper connector with 15cm (5.91") wire, for 10mm (0.39") tape, 3 pin



NCO-STMKB-3P-10
Strip to cable with black male & female connector, for 10mm (0.39") tape, 3 pin



NCO-STMKW-3P-10
Strip to cable with white male & female connector, for 10mm (0.39") tape, 3 pin



NI4CO-STS-3P-10
Strip to strip connector, for 10mm (0.39") tape, 3 pin

Additional Accessories (Optional, purchase for extra)



MCW-3P-67
Male connector with 30cm (0.98') white cable, 3 pin, IP67, Wet, 20 AWG



FCW-3P-67
Female connector with 30cm (0.98') white cable, 3 pin, IP67, Wet, 20 AWG



VHB
VHB 3M adhesive back tape, stronger stickiness